

Product Technical Information Sheet

Blockleys™

Charcoal Chamfered Pavers

Profile Paver Type:	Rectangular	Dimensions:	210 x 105 x 65 mm
Profile Arrises:	Chamfered	Dimensional Range:	R1
Abrasion Resistance:	A3	Dimensional Tolerance:	L:±6mm W:±4mm T:±3mm
Transverse Break Load:	T4	Dimensions Comment:	Dimensions include 3mm Spacer Nibs
Slip Skid Resistance:	U3	Reflectance Value Dry:	6.5
Freeze/Thaw Resistance:	FP100	Reflectance Value Wet:	5
Reaction to Fire:	Class A1 _(FL)	Acid Resistance:	Class C
External Fire Performance:	Class B _(ROOF)	Dangerous Substances:	N/A
Thermal Conductivity (P = 50):	0.72	W/m.K	Thermal Resistance (P = 50): 0.09 m ² .K/W
Thermal Conductivity (P = 90):	0.79	W/m.K	Thermal Resistance (P = 90): 0.08 m ² .K/W
Quantity per Pack:	400	Recycled Content:	0 %
Products per Square Metre:	46	Net Dry Density:	2290 kg/m ³
Product Weight:	3.08	kg	DoP common root reference code: --BL65PVB--

Clay pavers are manufactured and supplied to relevant clauses of **BS EN 1344**.

Declarations of performance, environmental and other policies can be found on the company website: www.mbhplc.co.uk. Further information is available via our sales department on 0844 931 0022 or email sales@mbhplc.co.uk.

