MICHELMERSH
Britain's Brick Specialists

Product Technical Information Sheet

Freshfield Lane™

Square Edge Pavers

Profile Paver Type:	Rectangular		Dimensions:	200 x 100 x 65 mm	
Profile Arrises:	Square Edged		Dimensional Range:	R1	
Abrasion Resistance:	A2		Dimensional Tolerance:	L:±6mm W:±4mm T:±3mm	
Transverse Break Load:	T2		Dimensions Comment:	n/a	
Slip Skid Resistance:	U3		Reflectance Value Dry:	12.5	
Freeze/Thaw Resistance:	FP100		Reflectance Value Wet:	7.2	
Reaction to Fire:	Class $A1_{(FL)}$		Acid Resistance:	NPD	
External Fire Performance:	Class $B_{(ROOF)}$		Dangerous Substances:	N/A	
Thermal Conductivity (P = 50):	0.45	W/m.K	Thermal Resistance (P = 50):	0.14	m².K/W
Thermal Conductivity (P = 90):	0.51	W/m.K	Thermal Resistance (P = 90):	0.13	m².K/W
Quantity per Pack:	400		Products per Square Metre:	50	
Net Dry Density:	1690	kg/m³	Product Weight:	2.225	kg
DoP common root reference code:	--FL65PVB--				

Clay pavers are manufactured and supplied to relevant clauses of BS EN 1344.

Declarations of performance, environmental and other policies can be found on the company website: **www.mbhplc.co.uk**. Further information is available via our sales department on 0844 931 0022 or email **sales@mbhplc.co.uk**.

Technical data correct at the time of issue. Please order a sample for accurate representation of product.

Issue Date: 10/01/24